



KenGen

KENYA ELECTRICITY GENERATING COMPANY PLC

RFx: 5000008655

KGN-GDD-204-2021

TENDER FOR SUPPLY OF DRILL STRING COMPONENTS, FISHING AND DIRECTIONAL TOOLS FOR GEOTHERMAL DEVELOPMENT DIVISION

(Citizen Contractors)

23rd December, 2021

ADDENDUM NO. 1:

In accordance with the **Tender for Supply of Drill String Components, Fishing and Directional Tools for Geothermal Development Division**, KenGen hereby issues addendum No. 1.

ADDITIONAL SCHEDULE E;

Section V - Schedule of Requirements

SCHEDULE E: LOAD HANDLING SLINGS AND ACCESSORIES

Item	Description	Unit	Qty
1	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 8 meters Wire rope: 1-1/4" diameter, 6x37 EIPS, IWRC. Eye loop (W x L): 10" x 20" Rated capacity (vertical pull): 15 tons	Piece	20
2	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 8 meters Wire rope: 1" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 8" x 16" Rated capacity (vertical pull): 9.8 tons	Piece	20
3	Single leg wire rope sling with swaged eye loop on both ends; Length: 8 meters Wire rope: 5/8" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 5" x 10" Rated capacity (vertical pull): 3.9 tons	Piece	20
4	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 1.5 meters Wire rope: 3/4" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 6" x 12" Rated capacity (vertical pull): 5.6 tons	Piece	5
5	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 1.7 meters Wire rope: 3/4" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 6" x 12" Rated capacity (vertical pull): 5.6 tons	Piece	5

6	Four (4) leg chain sling assembly complete with eye sling hooks with latches; Nominal size: 22 mm Material: Grade 80 alloy steel Length: 14 m Hooks: Crosby S-320 carbon steel eye hook or equivalent with latch, 15 tons working load limit Connecting link: Crosby A-1337 grade 100 alloy steel or equivalent connecting link for 22 mm chain.	Piece	5
7	Four (4) leg chain sling assembly complete with eye sling hooks with latches; Nominal size: 22 mm Material: Grade 80 alloy steel Length: 8 m Hooks: Crosby S-320 carbon steel eye hook or equivalent with latch, 15 tons working load limit Connecting link: Crosby A-1337 grade 100 alloy steel or equivalent connecting link for 22 mm chain.	Piece	5
8	Crosby G-209A or equivalent forged alloy steel screw pin anchor shackle; nominal size: 1-1/8", Working load limit: 15 tons	Piece	40
9	Crosby G-209A or equivalent forged alloy steel screw pin anchor shackle; Nominal size: 3/4", Working load limit: 7 tons	Piece	4
10	Crosby G-2130A or equivalent forged alloy steel bolt type anchor shackle; nominal size: 7/8", working load limit: 6.5 tons	Piece	4
11	Class 7, Type III, 2-ply polyester webbing sling; width: 4", length: 4 m Rated capacity (vertical): 5 tons	Piece	10
12	Class 7, Type III, 2-ply polyester webbing sling; width: 12", length: 10 m Rated capacity (vertical): 15 tons	Piece	10
13	Class 7, Type V (endless), 2-ply polyester webbing sling; width: 8", length: 10 m Rated capacity (vertical): 19 tons	Piece	10
14	3/4" diameter rotation-resistant wire rope, 19x7 construction, Galvanized, EIPS, wire strand core. To be supplied in 2 reels, each 600m long	Meter	1200 (2 x 600)
15	5/8" diameter wire rope, 6x36 Warrington Seale, Galvanized, Preformed, right ordinary lay, EIPS, IWRC. To be supplied in 4 reels, each 400m long	Meter	1600 (4 x 400)

PART II TECHNICAL SPECIFICATIONS

SCHEDULE E: LOAD HANDLING SLINGS AND ACCESSORIES

Item	Description
1	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 8 meters Wire rope: 1-1/4" diameter, 6x37 EIPS, IWRC. Eye loop (W x L): 10" x 20" Rated capacity (vertical pull): 15 tons
2	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 8 meters Wire rope: 1" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 8" x 16" Rated capacity (vertical pull): 9.8 tons
3	Single leg wire rope sling with swaged eye loop on both ends; Length: 8 meters Wire rope: 5/8" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 5" x 10" Rated capacity (vertical pull): 3.9 tons
4	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 1.5 meters Wire rope: 3/4" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 6" x 12" Rated capacity (vertical pull): 5.6 tons
5	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 1.7 meters Wire rope: 3/4" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 6" x 12" Rated capacity (vertical pull): 5.6 tons
6	Four (4) leg chain sling assembly complete with eye sling hooks with latches; Nominal size: 22 mm Material: Grade 80 alloy steel Length: 14 m Hooks: Crosby S-320 carbon steel eye hook or equivalent with latch, 15 tons working load limit Connecting link: Crosby A-1337 grade 100 alloy steel or equivalent connecting link for 22 mm chain.
7	Four (4) leg chain sling assembly complete with eye sling hooks with latches; Nominal size: 22 mm Material: Grade 80 alloy steel Length: 8 m Hooks: Crosby S-320 carbon steel eye hook or equivalent with latch, 15 tons working load limit Connecting link: Crosby A-1337 grade 100 alloy steel or equivalent connecting link for 22 mm chain.
8	Crosby G-209A or equivalent forged alloy steel screw pin anchor shackle; nominal size: 1-1/8", Working load limit: 15 tons
9	Crosby G-209A or equivalent forged alloy steel screw pin anchor shackle; Nominal size: 3/4", Working load limit: 7 tons
10	Crosby G-2130A or equivalent forged alloy steel bolt type anchor shackle; nominal size: 7/8", working load limit: 6.5 tons
11	Class 7, Type III, 2-ply polyester webbing sling; width: 4", length: 4 m Rated capacity (vertical): 5 tons

12	Class 7, Type III, 2-ply polyester webbing sling; width: 12", length: 10 m Rated capacity (vertical): 15 tons
13	Class 7, Type V (endless), 2-ply polyester webbing sling; width: 8", length: 10 m Rated capacity (vertical): 19 tons
14	3/4" diameter rotation-resistant wire rope, 19x7 construction, Galvanized, EIPS, wire strand core. To be supplied in 2 reels, each 600m long
15	5/8" diameter wire rope, 6x36 Warrington Seale, Galvanized, Preformed, right ordinary lay, EIPS, IWRC. To be supplied in 4 reels, each 400m long

ADDITIONAL SCHEDULE E

SCHEDULE E: LOAD HANDLING SLINGS AND ACCESSORIES

Item	Description	Unit	Qty	Unit Price	Total Price
1	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 8 meters Wire rope: 1-1/4" diameter, 6x37 EIPS, IWRC. Eye loop (W x L): 10" x 20" Rated capacity (vertical pull): 15 tons	Piece	20		
2	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 8 meters Wire rope: 1" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 8" x 16" Rated capacity (vertical pull): 9.8 tons	Piece	20		
3	Single leg wire rope sling with swaged eye loop on both ends; Length: 8 meters Wire rope: 5/8" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 5" x 10" Rated capacity (vertical pull): 3.9 tons	Piece	20		
4	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 1.5 meters Wire rope: 3/4" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 6" x 12" Rated capacity (vertical pull): 5.6 tons	Piece	5		
5	Single leg wire rope sling with swaged eye loop on both ends; Overall length: 1.7 meters Wire rope: 3/4" diameter, 6x19 EIPS, IWRC. Eye loop (W x L): 6" x 12" Rated capacity (vertical pull): 5.6 tons	Piece	5		
6	Four (4) leg chain sling assembly complete with eye sling hooks with latches; Nominal size: 22 mm Material: Grade 80 alloy steel Length: 14 m Hooks: Crosby S-320 carbon steel eye hook or equivalent with latch, 15 tons working load limit Connecting link: Crosby A-1337 grade 100 alloy steel or equivalent connecting link for 22 mm chain.	Piece	5		

7	Four (4) leg chain sling assembly complete with eye sling hooks with latches; Nominal size: 22 mm Material: Grade 80 alloy steel Length: 8 m Hooks: Crosby S-320 carbon steel eye hook or equivalent with latch, 15 tons working load limit Connecting link: Crosby A-1337 grade 100 alloy steel or equivalent connecting link for 22 mm chain.	Piece	5		
8	Crosby G-209A or equivalent forged alloy steel screw pin anchor shackle; nominal size: 1-1/8", Working load limit: 15 tons	Piece	40		
9	Crosby G-209A or equivalent forged alloy steel screw pin anchor shackle; Nominal size: 3/4", Working load limit: 7 tons	Piece	4		
10	Crosby G-2130A or equivalent forged alloy steel bolt type anchor shackle; nominal size: 7/8", working load limit: 6.5 tons	Piece	4		
11	Class 7, Type III, 2-ply polyester webbing sling; width: 4", length: 4 m Rated capacity (vertical): 5 tons	Piece	10		
12	Class 7, Type III, 2-ply polyester webbing sling; width: 12", length: 10 m Rated capacity (vertical): 15 tons	Piece	10		
13	Class 7, Type V (endless), 2-ply polyester webbing sling; width: 8", length: 10 m Rated capacity (vertical): 19 tons	Piece	10		
14	3/4" diameter rotation-resistant wire rope, 19x7 construction, Galvanized, EIPS, wire strand core. To be supplied in 2 reels, each 600m long	Meter	1200 (2 x 600)		
15	5/8" diameter wire rope, 6x36 Warrington Seale, Galvanized, Preformed, right ordinary lay, EIPS, IWRC. To be supplied in 4 reels, each 400m long	Meter	1600 (4 x 400)		
Sub Total					
Discount (%) if any					
Local Taxes e.g. Duty, VAT, GoK fees, etc					
Other Charges e.g transportation fees etc					
Total Cost (DDP) to Olkaria Rig Store					
Country of Origin					
Name of manufacturer					
Currency of Tender					
Delivery period to Olkaria Rig Store (after signing contract)					

SUMMARY OF PRICE SCHEDULES

SCHEDULES & DESCRIPTION		CURRENCY	AMOUNT
A	HEAVY WEIGHT DRILL PIPES & STABILIZERS		
B	DRILL COLLARS & SUBS		
C	DIRECTIONAL DRILLING TOOLS		
D	ASSORTED FISHING TOOLS		
E	LOAD HANDLING SLINGS AND ACCESSORIES		
TOTAL TENDER PRICE (to be Transferred to Tender Form)			

ACKNOWLEDGEMENT OF ADDENDUM NO.1

We, the undersigned hereby certify that the addendum is an integral part of the document and has been incorporated in the tender proposal.

Signed.....

Tenderer.....

Date.....